



Waterlogic Firewall™ Cube

The sophisticated Firewall Cube brings our breakthrough Firewall water purification to your office in a compact, modern design. The intuitive user interface allows you the option of cold, ambient, hot or extra hot water to satisfy all tastes.

Three Steps to Greatness

Your Waterlogic water purifier has 3 core technologies which mean that what you get out of your machine is much better than what goes in:



1. High Performance Filtration: Our filtration technology is really good at taking the bad stuff out and leaving the good stuff in. This stage removes chlorine and other waterborne tastes and odors.



2. Firewall™: Our Firewall advanced ultra violet light system purifies the water to 99.9999% bacteria free and acts as a final barrier to pathogens right at the point of dispense.



3. BioCote®: The Firewall Cube water treatment system is BioCote protected to provide an effective barrier against microbes like bacteria and mold, which may cause odors or staining.

*For more information visit www.biocote.com/home-us.



CLASS A
UV








FIREWALL
UV
SENSOR



Firewall Cube Features

- Ambient, cold, hot and extra hot water options
- Firewall UV purification guarantees 99.9999% bacteria free water, 100% of the time
- BioCote antimicrobial protection
- Certified ultraviolet microbiological water treatment system under NSF/ANSI-55 Class A and NSF P231
- Touch sensitive user interface



Water Options	Technical Features		
	Cube dimensions	11.6" (W) x 14.8" (H) x 16.7" (D) 296mm (W) x 375mm (H) x 425mm (D)	
	Dispense area height	9.75" (247mm) without drip tray 6.1" (155mm) with drip tray	
	Weight	18kg (39.6 lbs)	
	Standard filtration supplied	1 x Carbon Block (CBC) NSF-53 certified for lead, cyst, and asbestos reduction.	
Symbols	Additional features Firewall UV sensor Filter change alert Leak detection Sleep mode Thermal overload protection Energy Star	Capacity Cold: 0.308 gal (1.4 liter) tank Hot: 0.286 gal (1.3 liter) tank	
 Ambient water			Water temperatures Cold: 41-59°F / 5-15°C Hot: 87-95°C / 188.6-203°F
 Cold water			
 Hot water			
 Extra Hot water			
Compressor			

Tested and certified

 **NSF/ANSI-55 Class A**
Ultraviolet Microbiological
Water Treatment Systems

NSF P231
Protocol for
Microbiological Purifiers

NSF/ANSI-53
Health effects for lead,
cyst and asbestos reduction



CE QUALITY & SAFETY
GUARANTEED

Waterlogic International Limited and WLI Trading Limited reserves the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd is licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Speak to a water expert

AquaLine Pure Water Services, Inc.

15 Border Street
West Newton, MA 02465

Tel: 617.425.1999

www.aqualineboston.com